

DAFTAR PUSTAKA

1. Al-Allak H. M., J. Illingsworth, A. W. Brinkman, and J. Woods, "Current-voltage characteristics of donor-doped BaTiO₃ ceramics," *Journal of Physics D*, vol. 22, Sept. 1989, pp. 1393-1397.
2. Andrews, G.E.; Bradley, D.; Hundy. G. F., Hot wire anemometer calibration for measurements of small gas velocities: Int. J. Heat Mass Transfer: Val. 15. No. 1.0. (1972), pp. 1765- 1786.
3. Bradshaw P., Thermal methods of flow measurements, *Journal of Scientific Instruments (Journal of Physics E) Series 2*, Vol. 1 (1968), pp. 504-509.
4. Feustel, O.; Schmidt, W.: *Sensorhalbleiter und Schutzelemente, Auswahlkriterien und Berechnungshinweise* for Thermistoren und edelgasgefüllte Überspannungsableiter. Vogel Verlag, 1982.
5. Hanke, L: *Der keramische Kaltleiter*. Siemens AG Verlag, Erlangen, 1973.
6. Heywang W., "Resistivity anomaly in doped barium titanate," *Journal of the American Ceramic Society*, vol. 47, no. 10, 1964, pp. 484-490
7. Hill, D.; Tuller, H.: *Ceramic Sensors: Theory and Practice*. Ceramic Materials for Electronics, R. Buchanan, ed., Marcel Dekker, Inc., New York, 1991.
8. Horn, M., Umar L. Self-controlled PTC Sensor for Reliable Overfill Protection of Liquids. IMTC 2002 IEEE Instrumentation and Measurement Technology Conference. 21. -23. Mai, Anchorage Alaska USA, 2002.
9. Lazuardi Umar, Smart airflow measurement system with self control and self calibration, Final Report of Indonesia Toray Science Foundation (ITSF) 2005, February 2005.
10. Mallick Jr. G. T. and Emtage P. R., "Current-voltage characteristics of semiconducting barium titanate ceramics," *Journal of Applied Physics*, vol. 39, 1968, pp. 3088-3094.
11. Makinwa K., Huijsing J., A smart wind sensor based on thermal sigma-delta modulation techniques, *Sensors & Actuators A97-98* (2002), pp. 15-20.
12. Otto, J. 2002. *Methoden der Füllstandsmesstechnik, Eine aktuelle Übersicht*.

VDI-Berichte 1712, Füllstandmesstechnik in der industriellen Praxis, Tagung Frankfurt, 4.-5. Dezember.

13. Raouf Ismail, *Air velocity measurement using thermistor*, Cambridge AccuSense, Inc., Shirley, MA USA, 1999.
14. Roth, P.: Ceramic PTC thermistor as sensor, Level measurement made easy. Siemens Matsushita Components GmbH, München.
15. Schneider, G.; *Selbstüberwachung und Selbstkalibrierung von Sensoren*. Automatisierungstechnische Praxis atp 38, Heft 9 (1996), S. 9-17.
16. Sostmann, H.: Thermistor Thermometer. Fundamentals of Thermometry Part IV, *Isotech Journal of Thermometry*, Volume 8 No. 2 (1997), S. 66-84.
17. Stephen J Prosser and Ernest D.D. Schmidt, Smart sensors for *industrial applications*, *Microelectronic International* 16/2, 1999.
18. Trankler, H.-R: *Taschenbuch der Messtechnik mit Schwerpunkt Sensortechnik*. Oldenburg Verlag, 4.Auflage, 1996.
19. VDI 3519 Blatt 1-2. Füllstandmessung von Flüssigkeiten und Feststoffen (Schüttgütern). VDI/VDE Verlag, S. 27-32.
20. Veijola T., "Electrothermal simulation models for NTC and PTC thermistors", *Proceedings of CSC'98*, vol. 2, Greece, 1998, pp. 950-955.
21. Wise, J.A.: *Stability of Glass-Encapsulated Disc-Type Thermistors*. Temperature, Its Measurement and Control in Science and Industry, Vol. 6, James F. Schooley, ed., American Institute of Physics, New York, NY, p. 481, 1992.
22. Wood, S.D.: *An Investigation of the Stability of Thermistors*. J. Res. of the National Bureau of Standards, 83(247), 1978.